

101 Hessle Road Hull, HU3 2BN England T + 44 (0) 1482 225181 F + 44 (0) 1482 328326

www.smith-nephew.com



Tincture of Benzoin Pump Spray

Safety Data Sheet

according to Federal Register / Vol. 89, No. 98 / Monday, May 20, 2024 / Rules and Regulations SDS Reference Number: CSSS-TCO-010-164697

Issue date: 12/12/2024 Revision date: 12/12/2024 Version: 1.0

SECTION 1: Identification

1.1. Identification

Product form : Mixture

Product name : Tincture of Benzoin Pump Spray

1.2. Recommended use and restrictions on use

Recommended use : Skin Preparation
Restrictions on use : Not available

1.3. Supplier

Smith & Nephew Medical Ltd 101 Hessle Road Hull HU3 2BN United Kingdom T +44 (0)1482 225181

1.4. Emergency telephone number

Emergency number : Chemtrec: 1-800-424-9300, Local: +1-703-527-3887 (24 Hours)

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS US classification

Flammable liquids, Category 2

Skin corrosion/irritation, Category 2

H315

Causes skin irritation.

Serious eye damage/eye irritation, Category 2A

H319

Causes serious eye irritation.

Skin sensitisation, Category 1

H317

May cause an allergic skin reaction.

Specific target organ toxicity – Single exposure, Category 3, Narcosis

H336

May cause drowsiness or dizziness.

Full text of H-statements: see section 16

2.2. GHS Label elements, including precautionary statements

GHS US labelling

Hazard pictograms (GHS US)





Signal word (GHS US) : Danger

Hazard statements (GHS US) : H225 - Highly flammable liquid and vapour.

H315 - Causes skin irritation.

H317 - May cause an allergic skin reaction. H319 - Causes serious eye irritation.

Safety Data Sheet

according to Federal Register / Vol. 89, No. 98 / Monday, May 20, 2024 / Rules and Regulations

Precautionary statements (GHS US)

H336 - May cause drowsiness or dizziness.

: P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P233 - Keep container tightly closed.

P240 - Ground/Bond container and receiving equipment.

P241 - Use explosion-proof electrical/ventilating/lighting equipment.

P242 - Use only non-sparking tools.

P243 - Take precautionary measures against static discharge.

P261 - Avoid breathing dust/fume/gas/mist/vapours/spray.

P264 - Wash hands, forearms and face thoroughly after handling.

P271 - Use only outdoors or in a well-ventilated area.

P272 - Contaminated work clothing must not be allowed out of the workplace.

P280 - Wear protective gloves/protective clothing/eye protection/face protection.

P302+P352 - If on skin: Wash with plenty of water.

P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing. P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing. P312 - Call a poison center or doctor if you feel unwell.

P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.

P337+P313 - If eye irritation persists: Get medical advice/attention.

P362+P364 - Take off contaminated clothing and wash it before reuse.

P363 - Wash contaminated clothing before reuse.

P370+P378 - In case of fire: Use alcohol resistant foam, dry extinguishing powder, carbon dioxide (CO2) to extinguish.

P403+P233 - Store in a well-ventilated place. Keep container tightly closed.

P403+P235 - Store in a well-ventilated place. Keep cool.

P405 - Store locked up.

P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS US)

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	GHS US classification
2-Propanol	CAS-No.: 67-63-0	75 – 100	Flam. Liq. 2, H225 Eye Irrit. 2A, H319 STOT SE 3, H336
Gum benzoin -	CAS-No.: 9000-05-9		Skin Irrit. 2, H315 Eye Irrit. 2A, H319 Skin Sens. 1, H317

Safety Data Sheet

according to Federal Register / Vol. 89, No. 98 / Monday, May 20, 2024 / Rules and Regulations

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures general : Call a poison center or a doctor if you feel unwell.

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. If breathing stops, give artificial

respiration. If unconscious, place in the recovery position and seek medical advice.

First-aid measures after skin contact : Rinse skin with water/shower. Take off immediately all contaminated clothing. If skin irritation or

rash occurs: Get medical advice/attention.

First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to

do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

First-aid measures after ingestion : Do NOT induce vomiting. Get immediate medical advice/attention.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects : May cause drowsiness or dizziness.

Symptoms/effects after inhalation : Although no appropriate human or animal health effects data are known to exist, this material is

expected to be an inhalation hazard.

Symptoms/effects after skin contact : Irritation. May cause an allergic skin reaction.

Symptoms/effects after eye contact : Eye irritation.

Symptoms/effects after ingestion : None under normal conditions.

4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Dry powder. Alcohol-resistant foam. Carbon dioxide.

Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Specific hazards arising from the chemical

Fire hazard : Highly flammable liquid and vapour.

Explosion hazard : No direct explosion hazard. Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions : Fight fire from safe distance and protected location. Do not enter fire area without proper

protective equipment, including respiratory protection.

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing

apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Stop leak if safe to do so. Notify authorities if product enters sewers or public waters. Absorb spillage to prevent material damage.

Safety Data Sheet

according to Federal Register / Vol. 89, No. 98 / Monday, May 20, 2024 / Rules and Regulations

6.1.1. For non-emergency personnel

Protective equipment : Wear recommended personal protective equipment.

Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid breathing

dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer

to section 8: "Exposure controls/personal protection".

Emergency procedures : Evacuate unnecessary personnel. Stop leak if safe to do so.

6.2. Environmental precautions

Avoid release to the environment. Do not allow to enter drains or water courses.

6.3. Methods and material for containment and cleaning up

For containment : Absorb spilled material with sand or earth. Contain any spills with dikes or absorbents to prevent

migration and entry into sewers or streams. Stop leak without risks if possible.

Methods for cleaning up : Take up liquid spill into absorbent material, e.g.: sand, earth, vermiculite.

Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed : Not expected to present a significant hazard under anticipated conditions of normal use.

Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapours may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Use only outdoors or in a well-ventilated area. Avoid breathing dust/fume/gas/mist/vapours/spray. Avoid

contact with skin and eyes.

Hygiene measures : Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed

out of the workplace. Do not eat, drink or smoke when using this product. Always wash hands

after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Ground/bond container and receiving equipment.

Storage conditions : Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up. Store

in a dry place. Keep away from naked flames/heat.

Storage temperature : \leq 25 °C

Packaging materials : Store always product in container of same material as original container.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Safety Data Sheet

according to Federal Register / Vol. 89, No. 98 / Monday, May 20, 2024 / Rules and Regulations

2-Propanol (67-63-0)		
USA - ACGIH - Occupational Exposure Limits		
Local name	2-Propanol	
ACGIH OEL TWA	200 ppm	
ACGIH OEL STEL	400 ppm	
Remark (ACGIH)	TLV® Basis: Eye & URT irr; CNS impair. Notations: A4 (Not classifiable as a Human Carcinogen); BEI	
Regulatory reference	ACGIH 2024	
USA - ACGIH - Biological Exposure Indices		
Local name	2-Propanol	
BEI	40 mg/l Parameter: Acetone - Medium: urine - Sampling time: End of shift at end of workweek - Notations: B, Ns	
Regulatory reference	ACGIH 2024	
USA - OSHA - Occupational Exposure Limits		
Local name	Isopropyl alcohol	
OSHA PEL TWA	980 mg/m³	
	400 ppm	
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1	

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.

Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment:

Wear recommended personal protective equipment.

Hand protection:

Protective gloves

Eye protection:

Safety glasses

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

Personal protective equipment symbol(s):







Safety Data Sheet

according to Federal Register / Vol. 89, No. 98 / Monday, May 20, 2024 / Rules and Regulations

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid Appearance : Liquid.

Colour : Transparent amber
Odour : characteristic
Odour threshold : No data available
pH : No data available
Melting point : No tapplicable
Freezing point : No data available
Boiling point : No data available

Flash point : 11.7 °C

Relative evaporation rate (butylacetate=1) : No data available : No data available Flammability (solid, gas) Vapour pressure No data available Relative vapour density at 20°C No data available Relative density 0.85 (25°C) Solubility Miscible with water. Partition coefficient n-octanol/water (Log Pow) : No data available Auto-ignition temperature : No data available Decomposition temperature : No data available Viscosity, kinematic : No data available Viscosity, dynamic : No data available

Explosive limits : Lower explosion limit: 2.5 vol %

Upper explosion limit: 12 vol %

Explosive properties : No data available Oxidising properties : No data available

9.2. Other information

Volatility : 93 %

SECTION 10: Stability and reactivity

10.1. Reactivity

Highly flammable liquid and vapour.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

Strong oxidizing agents.

Safety Data Sheet

according to Federal Register / Vol. 89, No. 98 / Monday, May 20, 2024 / Rules and Regulations

10.6. Hazardous decomposition products

On combustion, forms: carbon oxides (CO and CO2).

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified Acute toxicity (dermal) : Not classified Acute toxicity (inhalation) : Not classified

2-Propanol (67-63-0)

LD50 oral rat	5.84 g/kg
LD50 dermal rabbit	16.4 ml/kg

Skin corrosion/irritation: Causes skin irritation.Serious eye damage/irritation: Causes serious eye irritation.Respiratory or skin sensitisation: May cause an allergic skin reaction.

Germ cell mutagenicity : Not classified Carcinogenicity : Not classified

Tincture of Benzoin Pump Spray

IARC group	Not applicable
National Toxicity Program (NTP) Status	Not applicable

Reproductive toxicity : Not classified

STOT-single exposure : May cause drowsiness or dizziness.

STOT-repeated exposure : Not classified
Aspiration hazard : Not classified

Symptoms/effects : May cause drowsiness or dizziness.

Symptoms/effects after inhalation : Although no appropriate human or animal health effects data are known to exist, this material is

expected to be an inhalation hazard.

Symptoms/effects after skin contact : Irritation. May cause an allergic skin reaction.

Symptoms/effects after eye contact : Eye irritation.

Symptoms/effects after ingestion : None under normal conditions.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms nor to cause long-term adverse

effects in the environment.

2-Propanoi (67-63-0)	
LC50 96h - Fish [1]	9640 mg/ l

12.2. Persistence and degradability

No additional information available

-1 (07 02 0)

12.3. Bioaccumulative potential

No additional information available

Safety Data Sheet

according to Federal Register / Vol. 89, No. 98 / Monday, May 20, 2024 / Rules and Regulations

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Disposal methods

Regional waste regulation : Disposal must be done according to official regulations.

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

Sewage disposal recommendations : Disposal must be done according to official regulations. Product/Packaging disposal recommendations : Disposal must be done according to official regulations.

Additional information : Flammable vapours may accumulate in the container. Do not re-use empty containers.

SECTION 14: Transport information

In accordance with DOT / TDG / IMDG / IATA

14.1. UN number

 UN-No.(DOT)
 : UN1993

 UN-No. (TDG)
 : UN1993

 UN-No. (IMDG)
 : 1993

 UN-No. (IATA)
 : 1993

14.2. UN proper shipping name

Proper Shipping Name (DOT) : Flammable liquids, n.o.s. (2-Propanol)
Proper Shipping Name (TDG) : FLAMMABLE LIQUID, N.O.S. (2-Propanol)
Proper Shipping Name (IMDG) : FLAMMABLE LIQUID, N.O.S. (2-Propanol)
Proper Shipping Name (IATA) : Flammable liquid, n.o.s. (2-Propanol)

14.3. Transport hazard class(es)

DOT

Transport hazard class(es) (DOT) : 3
Hazard labels (DOT) : 3



TDG

Transport hazard class(es) (TDG) : 3
Hazard labels (TDG) : 3



Safety Data Sheet

according to Federal Register / Vol. 89, No. 98 / Monday, May 20, 2024 / Rules and Regulations

IMDG

Transport hazard class(es) (IMDG) : 3
Danger labels (IMDG) : 3



IATA

Transport hazard class(es) (IATA) : 3
Danger labels (IATA) : 3



14.4. Packing group

Packing group (DOT) : II
Packing group (TDG) : II
Packing group (IMDG) : II
Packing group (IATA) : II

14.5. Environmental hazards

Other information : No supplementary information available.

14.6. Special precautions for user

DOT

UN-No.(DOT) : UN1993

DOT Special Provisions (49 CFR 172.102) : IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite

(31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized.

T7 - 4 178.274(d)(2) Normal..... 178.275(d)(3)

TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = 97 / (1 + a (tr - tf)) Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling.

TP8 - A portable tank having a minimum test pressure of 1.5 bar (150 kPa) may be used when

the flash point of the hazardous material transported is greater than 0 C (32 F).

TP28 - A portable tank having a minimum test pressure of 2.65 bar (265 kPa) may be used provided the calculated test pressure is 2.65 bar or less based on the MAWP of the hazardous material, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the

MAWP.

DOT Packaging Exceptions (49 CFR 173.xxx) : 150
DOT Packaging Non Bulk (49 CFR 173.xxx) : 202
DOT Packaging Bulk (49 CFR 173.xxx) : 242
DOT Quantity Limitations Passenger aircraft/rail (49 : 5 L

CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49

CFR 175.75)

PED 475 75

DOT Vessel Stowage Location

: B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this

section is exceeded.

Safety Data Sheet

according to Federal Register / Vol. 89, No. 98 / Monday, May 20, 2024 / Rules and Regulations

TDG

UN-No. (TDG) : UN1993

TDG Special Provisions : 16 - (1) The technical name of at least one of the most dangerous substances that predominantly contributes to the danger or dangers posed by the dangerous goods must be shown, in

parentheses, on the shipping document following the shipping name in accordance with clause 3.5(1)(c)(ii)(A). The technical name must also be shown, in parentheses, on a small means of containment or on a tag following the shipping name in accordance with subsections 4.11(2) and

(3).

(2) Despite subsection (1), the technical name for the following dangerous goods is not required to be shown on a shipping document or on a small means of containment when Canadian law for domestic transport or an international convention for international transport prohibits the disclosure of the technical name:

(a) UN1544, ALKALOID SALTS, SOLID, N.O.S. or ALKALOIDS, SOLID, N.O.S;

(b) UN1851, MEDICINE, LIQUID, TOXIC, N.O.S;

(c) UN3140, ALKALOID SALTS, LIQUID, N.O.S. or ALKALOIDS, LIQUID, N.O.S;

(d) UN3248, MEDICINE, LIQUID, FLAMMABLE, TOXIC, N.O.S; or

(e) UN3249, MEDICINE, SOLID, TOXIC, N.O.S.

(3) Despite subsection (1), the technical name for the following dangerous goods is not required to be shown on a small means of containment:

(a) UN2814, INFECTIOUS SUBSTANCE, AFFECTING HUMANS; or

(b) UN2900, INFECTIOUS SUBSTANCE, AFFECTING ANIMALS, 150 - An approved ERAP is required for the dangerous goods referred to in paragraph 7.2(1)(f) of Part 7 (Emergency

Response Assistance Plan).

Explosive Limit and Limited Quantity Index : 1 L
Excepted quantities (TDG) : E2
Passenger Carrying Road Vehicle or Passenger : 5 L

Carrying Railway Vehicle Index

Emergency Response Guide (ERG) Number : 128

IMDG

Special provisions (IMDG) : 274
Limited quantities (IMDG) : 1 L
Excepted quantities (IMDG) : E2
Packing instructions (IMDG) : P001
IBC packing instructions (IMDG) : IBC02
Tank instructions (IMDG) : T7

Tank special provisions (IMDG) : TP1, TP28, TP8

EmS-No. (Fire) : F-E - FIRE SCHEDULE Echo - NON-WATER-REACTIVE FLAMMABLE LIQUIDS EmS-No. (Spillage) : S-E - SPILLAGE SCHEDULE Echo - FLAMMABLE LIQUIDS, FLOATING ON WATER

Stowage category (IMDG) : B

IATA

PCA Excepted quantities (IATA) : E2 PCA Limited quantities (IATA) : Y341 PCA limited quantity max net quantity (IATA) : 1L PCA packing instructions (IATA) : 353 PCA max net quantity (IATA) : 5L CAO packing instructions (IATA) : 364 CAO max net quantity (IATA) : 60L Special provisions (IATA) A3 ERG code (IATA) 3H

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

Safety Data Sheet

according to Federal Register / Vol. 89, No. 98 / Monday, May 20, 2024 / Rules and Regulations

SECTION 15: Regulatory information

15.1. US Federal regulations

Tincture of Benzoin Pump Spray		
SARA Section 311/312 Hazard Classes	Physical hazard - Flammable (gases, aerosols, liquids, or solids) Health hazard - Specific target organ toxicity (single or repeated exposure) Health hazard - Skin corrosion or Irritation Health hazard - Respiratory or skin sensitization Health hazard - Serious eye damage or eye irritation	

Commercial status of components according to the United States Environmental Protection Agency's Toxic Substances Control Act (TSCA):

Name	CAS-No.	Listing	Commercial status	Flags
2-Propanol	67-63-0	Present	Active	
Gum benzoin -	9000-05-9	Present	Active	

2-Propanol (67-63-0)

Subject to reporting requirements of United States SARA Section 313

15.2. International regulations

CANADA

2-Propanol (67-63-0)

Listed on the Canadian DSL (Domestic Substances List)

Gum benzoin - (9000-05-9)

Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations

No additional information available

National regulations

2-Propanol (67-63-0)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

15.3. US State regulations

No additional information available

SECTION 16: Other information

according to Federal Register / Vol. 89, No. 98 / Monday, May 20, 2024 / Rules and Regulations

Revision date : 12/12/2024

Full text of hazard	Full text of hazard classes and H-statements	
H225	Highly flammable liquid and vapour.	
H315	Causes skin irritation.	

Safety Data Sheet

according to Federal Register / Vol. 89, No. 98 / Monday, May 20, 2024 / Rules and Regulations

Full text of hazard	Full text of hazard classes and H-statements	
H317	May cause an allergic skin reaction.	
H319	Causes serious eye irritation.	
H336	May cause drowsiness or dizziness.	

Safety Data Sheet (SDS), USA

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.