

Smith & Nephew Medical Limited
101 Hessle Road
Hull, HU3 2BN
England

T + 44 (0) 1482 225181
F + 44 (0) 1482 328326
www.smith-nephew.com

REMOVE – Universal Adhesive Remover

Safety Data Sheet

according to Federal Register / Vol. 89, No. 98 / Monday, May 20, 2024 / Rules and Regulations
SDS Reference Number: CSSS-TCO-010-164807
Issue date: 1/14/2025 Revision date: 1/14/2025 Version: 1.0

SECTION 1 Identification

1.1. Product identifier

Product form : Mixture
Product name : REMOVE – Universal Adhesive Remover
Product code : 403300

1.2. Other means of identification

No additional information available

1.3. Recommended use of the chemical and restrictions on use

Recommended use : Topical adhesive remover
Restrictions on use : Not available

1.4. Supplier's details

Smith & Nephew Medical Ltd
101 Hessle Road Hull HU3 2BN United Kingdom
T +44 (0)1482 225181 (24 Hours)

1.5. Emergency phone number

Emergency number : 911 (24 Hours)
1-800-424-9300 (Chemtrec 24 Hours)

1.6. Contact web address (all markets):

Contact web address : <https://www.smith-nephew.com/en/contact-us#general>

SECTION 2 Hazard Identification

2.1. Classification of the substance or mixture

GHS US classification

Flammable liquid, Category 3	H226	Flammable liquid and vapor.
Germ cell mutagenicity, Category 1B	H340	May cause genetic defects.
Carcinogenicity, Category 1B	H350	May cause cancer.

Document Number: 2009238
Document Version: 06

Document Part: 000
Document Status: Released

REMOVE – Universal Adhesive Remover

Safety Data Sheet

according to Federal Register / Vol. 89, No. 98 / Monday, May 20, 2024 / Rules and Regulations

Aspiration hazard, Category 1

H304

May be fatal if swallowed and enters airways.

Full text of H statements : see section 16

2.2. Label elements

GHS US labeling

Hazard pictograms (GHS US)

:



Signal word (GHS US)

: Danger

Hazard statements (GHS US)

: H226 - Flammable liquid and vapor

H304 - May be fatal if swallowed and enters airways

H340 - May cause genetic defects.

H350 - May cause cancer.

Precautionary statements (GHS US)

: P201 - Obtain special instructions before use.

P202 - Do not handle until all safety precautions have been read and understood.

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P233 - Keep container tightly closed.

P240 - Ground/Bond container and receiving equipment.

P241 - Use explosion-proof equipment.

P242 - Use non-sparking tools.

P243 - Take action to prevent static discharges.

P280 - Wear protective gloves, protective clothing, eye protection, face protection, and hearing protection.

P301+P310 - If swallowed: Immediately call a poison center or doctor.

P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P308+P313 - If exposed or concerned: Get medical advice/attention.

P331 - Do NOT induce vomiting.

P370+P378 - In case of fire: Use carbon dioxide (CO2), dry extinguishing powder, foam to extinguish.

P403+P235 - Store in a well-ventilated place. Keep cool.

P405 - Store locked up.

P501 - Dispose of contents and/or container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulations.

2.3. Hazards associated with known or reasonably anticipated uses

No additional information available

2.4. Hazards not otherwise classified

No additional information available

2.5. Unknown acute toxicity

No additional information available

Document Number: 2009238
Document Version: 06

Document Part: 000
Document Status: Released

REMOVE – Universal Adhesive Remover

Safety Data Sheet

according to Federal Register / Vol. 89, No. 98 / Monday, May 20, 2024 / Rules and Regulations

SECTION 3 Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	GHS US classification
Propanol, 1(or 2)-(2-methoxymethylethoxy)-	CAS-No.: 34590-94-8	50	Not classified
2-Propanol, 1-(2-methoxypropoxy)-	CAS-No.: 13429-07-7		Not classified
Naphtha (petroleum), hydrotreated heavy	CAS-No.: 64742-48-9	48.575	Muta. 1B, H340 Carc. 1B, H350 Asp. Tox. 1, H304
Alkanes, C9-12-iso-	CAS-No.: 90622-57-4		Flam. Liq. 3, H226 Asp. Tox. 1, H304
Benzenemethanol	CAS-No.: 100-51-6	0.1	Acute Tox. 4 (Oral), H302 Eye Irrit. 2A, H319 Skin Sens. 1B, H317

Full text of hazard classes and H-statements : see section 16

SECTION 4 First aid measures

4.1. Description of necessary first-aid measures

First-aid measures general	: Call a physician immediately.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. In case of irregular breathing or respiratory arrest provide artificial respiration.
First-aid measures after skin contact	: If skin irritation or rash occurs: Get medical advice/attention. Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: If the person is fully conscious, make him/her drink water. Never give an unconscious person anything to drink. Call a physician immediately. Do not induce vomiting/risk of damage to lungs exceeds poisoning risk.

4.2. Most important symptoms/effects, acute and delayed

Symptoms/effects after inhalation	: None under normal conditions.
Symptoms/effects after skin contact	: None under normal conditions.
Symptoms/effects after eye contact	: None under normal conditions.
Symptoms/effects after ingestion	: Risk of lung edema.

4.3. Indication of immediate medical attention and special treatment needed, if necessary

Other medical advice or treatment	: Treat symptomatically.
-----------------------------------	--------------------------

Document Number: 2009238
Document Version: 06

Document Part: 000
Document Status: Released

REMOVE – Universal Adhesive Remover

Safety Data Sheet

according to Federal Register / Vol. 89, No. 98 / Monday, May 20, 2024 / Rules and Regulations

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

- | | |
|--------------------------------|---|
| Suitable extinguishing media | : Dry powder. Foam. Carbon dioxide. |
| Unsuitable extinguishing media | : Do not use a water jet since it may cause the fire to spread. |

5.2. Specific hazards arising from the chemical

- | | |
|--|--------------------------------|
| Fire hazard | : Flammable liquid and vapor. |
| Explosion hazard | : No direct explosion hazard. |
| Hazardous decomposition products in case of fire | : Toxic fumes may be released. |

5.3. Special protective equipment and precautions for fire-fighters

- | | |
|--------------------------------|---|
| Firefighting instructions | : Fight fire from safe distance and protected location. Do not enter fire area without proper protective equipment, including respiratory protection. |
| Protection during firefighting | : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing. |

SECTION 6 Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- | | |
|------------------|---|
| General measures | : Stop leak if safe to do so. Notify authorities if product enters sewers or public waters. Absorb spillage to prevent material-damage. |
|------------------|---|

For non-emergency personnel

- | | |
|----------------------|--|
| Protective equipment | : Wear recommended personal protective equipment. |
| Emergency procedures | : No open flames, no sparks, and no smoking. Only qualified personnel equipped with suitable protective equipment may intervene. |

For emergency responders

- | | |
|---------------------------|---|
| Protective equipment | : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection". |
| Emergency procedures | : Evacuate unnecessary personnel. Stop leak if safe to do so. |
| Environmental precautions | : Avoid release to the environment. Notify authorities if product enters sewers or public waters. |

6.2. Methods and materials for containment and cleaning up

- | | |
|-------------------------|---|
| For containment | : Absorb spilled material with sand or earth. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Stop leak, if possible without risk. |
| Methods for cleaning up | : Wipe up with absorbent material (for example cloth). Cover spill with non combustible material, e.g.: sand/earth. |
| Other information | : Dispose of materials or solid residues at an authorized site. |
- For further information refer to section 13

Document Number: 2009238
Document Version: 06

Document Part: 000
Document Status: Released

REMOVE – Universal Adhesive Remover

Safety Data Sheet

according to Federal Register / Vol. 89, No. 98 / Monday, May 20, 2024 / Rules and Regulations

SECTION 7 Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling
- : Ensure good ventilation of the work station. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapors may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Take all necessary technical measures to avoid or minimize the release of the product on the workplace. Limit quantities of product at the minimum necessary for handling and limit the number of exposed workers. Provide local exhaust or general room ventilation. Floors, walls and other surfaces in the hazard area must be cleaned regularly.
- Hygiene measures
- : Separate working clothes from town clothes. Launder separately. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.
- Additional hazards when processed
- : Not expected to present a significant hazard under anticipated conditions of normal use.

7.2. Conditions for safe storage, including incompatibilities

- Technical measures
- : Ground/bond container and receiving equipment.
- Storage conditions
- : Store in a dry place. Store in a well-ventilated place. Keep cool. Keep container tightly closed. Keep away from naked flames/heat. Store locked up.
- Storage temperature
- : ≤ 25 °C
- Packaging materials
- : Store always product in container of same material as original container.

SECTION 8 Exposure controls/personal protection

8.1. Control parameters

Propanol, 1(or 2)-(2-methoxymethylethoxy)- (34590-94-8)	
USA - ACGIH - Occupational Exposure Limits	
Local name	Dipropylene glycol methyl ether (DPGME)
ACGIH OEL TWA	50 ppm
Remark (ACGIH)	TLV® Basis: Liver & CNS eff
Regulatory reference	ACGIH 2024
USA - OSHA - Occupational Exposure Limits	
Local name	Dipropylene glycol methyl ether
OSHA PEL TWA	600 mg/m³
	100 ppm
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1

Document Number:2009238

Document Part:000

Document Version:06

Document Status:Released

REMOVE – Universal Adhesive Remover

Safety Data Sheet

according to Federal Register / Vol. 89, No. 98 / Monday, May 20, 2024 / Rules and Regulations

Propanol, 1(or 2)-(2-methoxymethylethoxy)- (34590-94-8)

USA - Cal/OSHA - Occupational Exposure Limits

Local name	Dipropylene glycol methyl ether
Cal/OSHA PEL (OEL TWA)	600 mg/m ³
	100 ppm
Cal/OSHA STEL	900 mg/m ³
	150 ppm
Remark (Cal/OSHA)	S - Skin notation and Protecting Clothing
Regulatory reference	California Division of Occupational Safety and Health (Cal/OSHA) - Permissible Exposure Limit for Chemical Contaminants (Table AC-1)

USA - NIOSH - Occupational Exposure Limits

Local name	Dipropylene glycol methyl ether
NIOSH REL 10h TWA	100 ppm
NIOSH REL STEL	150 ppm
Regulatory reference (US-NIOSH)	OSHA Annotated Table Z-1 (NIOSH Pocket Guide to Chemical Hazards (NPG))

2-Propanol, 1-(2-methoxypropoxy)- (13429-07-7)

USA - ACGIH - Occupational Exposure Limits

Local name	Dipropylene glycol methyl ether (DPGME)
ACGIH OEL TWA	50 ppm
Remark (ACGIH)	TLV® Basis: Liver & CNS eff
Regulatory reference	ACGIH 2024

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.
Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures, such as personal protective equipment

Personal protective equipment:

Wear recommended personal protective equipment.

Hand protection:

Protective gloves

Eye protection:

Safety glasses

Document Number: 2009238
Document Version: 06

Document Part: 000
Document Status: Released

REMOVE – Universal Adhesive Remover

Safety Data Sheet

according to Federal Register / Vol. 89, No. 98 / Monday, May 20, 2024 / Rules and Regulations

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

[In case of inadequate ventilation] wear respiratory protection.

Personal protective equipment symbol(s):



SECTION 9 Physical and chemical properties

9.1. Basic physical and chemical properties

Physical state	: Liquid
Appearance	: Liquid.
Color	: No data available
Odor	: Slight Paraffinic
Odor threshold	: No data available
pH	: 3.8 (20°C)
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: > 177 °C
Flash point	: 45.6 °C
Relative evaporation rate (ether=1)	: < 1
Flammability (solid, gas)	: Not applicable.
Vapor pressure	: < 10 mm Hg
Relative vapor density at 20°C	: No data available
Relative density	: > 1
Solubility	: Soluble in water.
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Explosion limits	: Lower explosion limit: 0.6 vol % Upper explosion limit: 6.5 vol %
Explosive properties	: Not explosive.
Oxidizing properties	: Non oxidizing material.
Particle characteristics	: No data available

9.2. Data relevant with regard to physical hazard classes (supplemental)

Refractive index	: 1.416 (25°C)
------------------	----------------

Document Number: 2009238
Document Version: 06

Document Part: 000
Document Status: Released

REMOVE – Universal Adhesive Remover

Safety Data Sheet

according to Federal Register / Vol. 89, No. 98 / Monday, May 20, 2024 / Rules and Regulations

SECTION 10 Stability and reactivity

10.1. Reactivity

Flammable liquid and vapor.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Incompatible materials. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

10.5. Incompatible materials

Strong alkalis. Strong acids. Strong oxidizing agents. Halogens. Hydrogen peroxide.

10.6. Hazardous decomposition products

On burning: release of (highly) toxic gases/vapors.

SECTION 11 Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

Naphtha (petroleum), hydrotreated heavy (64742-48-9)

LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
LC50 Inhalation - Rat	> 5610 mg/m ³ 4 h

Skin corrosion/irritation : Not classified
Serious eye damage/irritation : Not classified
Respiratory or skin sensitization : Not classified
Germ cell mutagenicity : May cause genetic defects.
Carcinogenicity : May cause cancer.
Reproductive toxicity : Not classified
STOT-single exposure : Not classified

Document Number: 2009238
Document Version: 06

Document Part: 000
Document Status: Released

REMOVE – Universal Adhesive Remover

Safety Data Sheet

according to Federal Register / Vol. 89, No. 98 / Monday, May 20, 2024 / Rules and Regulations

STOT-repeated exposure	: Not classified
Aspiration hazard	: May be fatal if swallowed and enters airways.
Symptoms/effects after inhalation	: None under normal conditions.
Symptoms/effects after skin contact	: None under normal conditions.
Symptoms/effects after eye contact	: None under normal conditions.
Symptoms/effects after ingestion	: Risk of lung edema.

SECTION 12 Ecological information

12.1. Ecotoxicity

Ecology - general	: The product is not considered harmful to aquatic organisms or to cause long-term adverse effects in the environment.
Hazardous to the aquatic environment, short-term (acute)	: Not classified
Hazardous to the aquatic environment, long-term (chronic)	: Not classified

Naphtha (petroleum), hydrotreated heavy (64742-48-9)

LL50 96h - Fish [1]	10 mg/l
EL50 48h - Crustacea [1]	4.5 mg/l
EL50 72h - Algae [1]	3.1 mg/l

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Ozone	: Not classified
Fluorinated greenhouse gases	: No

SECTION 13 Disposal considerations

Regional waste regulation	: Disposal must be done according to official regulations.
Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Sewage disposal recommendations	: Disposal must be done according to official regulations.
Product/Packaging disposal recommendations	: Disposal must be done according to official regulations.
Additional information	: Flammable vapors may accumulate in the container. Do not re-use empty containers.

Document Number: 2009238
Document Version: 06

Document Part: 000
Document Status: Released

REMOVE – Universal Adhesive Remover

Safety Data Sheet

according to Federal Register / Vol. 89, No. 98 / Monday, May 20, 2024 / Rules and Regulations

SECTION 14 Transport information

In accordance with DOT / TDG / IMDG / IATA

14.1. UN number

UN-No.(DOT)	: UN1268
UN-No. (TDG)	: UN1268
UN-No. (IMDG)	: 1268
UN-No. (IATA)	: 1268

14.2. UN Proper Shipping Name

Proper Shipping Name (DOT)	: Petroleum distillates, n.o.s. (Naphtha (petroleum), hydrotreated heavy)
Proper Shipping Name (TDG)	: PETROLEUM DISTILLATES, N.O.S. (Naphtha (petroleum), hydrotreated heavy)
Proper Shipping Name (IMDG)	: PETROLEUM DISTILLATES, N.O.S. (Naphtha (petroleum), hydrotreated heavy)
Proper Shipping Name (IATA)	: Petroleum distillates, n.o.s. (Naphtha (petroleum), hydrotreated heavy)

14.3. Transport hazard class(es)

DOT

Transport hazard class(es) (DOT)	: 3
Hazard labels (DOT)	: 3



TDG

Transport hazard class(es) (TDG)	: 3
Hazard labels (TDG)	: 3



IMDG

Transport hazard class(es) (IMDG)	: 3
Hazard labels (IMDG)	: 3



IATA

Transport hazard class(es) (IATA)	: 3
Hazard labels (IATA)	: 3

Document Number:	2009238
Document Version:	06

Document Part:	000
Document Status:	Released

REMOVE – Universal Adhesive Remover

Safety Data Sheet

according to Federal Register / Vol. 89, No. 98 / Monday, May 20, 2024 / Rules and Regulations



14.4. Packing group

Packing group (DOT)	: III
Packing group (TDG)	: III
Packing group (IMDG)	: III
Packing group (IATA)	: III

14.5. Environmental hazards

Other information	: No supplementary information available.
-------------------	---

14.6. Transport in bulk

Not applicable

14.7. Special precautions for user

DOT

UN-No.(DOT)	: UN1268
DOT Special Provisions (49 CFR 172.102)	: 144 - If transported as a residue in an underground storage tank (UST), as defined in 40 CFR 280.12, that has been cleaned and purged or rendered inert according to the American Petroleum Institute (API) Standard 1604 (IBR, see 171.7 of this subchapter), then the tank and this material are not subject to any other requirements of this subchapter. However, sediments remaining in the tank that meet the definition for a hazardous material are subject to the applicable regulations of this subchapter. B1 - If the material has a flash point at or above 38 C (100 F) and below 93 C (200 F), then the bulk packaging requirements of 173.241 of this subchapter are applicable. If the material has a flash point of less than 38 C (100 F), then the bulk packaging requirements of 173.242 of this subchapter are applicable. IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672). T4 - 2.65 178.274(d)(2) Normal..... 178.275(d)(3) TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = $97 / 1 + a (tr - tf)$ Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling. TP29 - A portable tank having a minimum test pressure of 1.5 bar (150.0 kPa) may be used provided the calculated test pressure is 1.5 bar or less based on the MAWP of the hazardous materials, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP.
DOT Packaging Exceptions (49 CFR 173.xxx)	: 150
DOT Packaging Non Bulk (49 CFR 173.xxx)	: 203
DOT Packaging Bulk (49 CFR 173.xxx)	: 242

Document Number: 2009238
Document Version: 06

Document Part: 000
Document Status: Released

REMOVE – Universal Adhesive Remover

Safety Data Sheet

according to Federal Register / Vol. 89, No. 98 / Monday, May 20, 2024 / Rules and Regulations

DOT Quantity Limitations Passenger aircraft/rail (49 : 60 L

CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : 220 L

CFR 175.75)

DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.

TDG

UN-No. (TDG) : UN1268

TDG Special Provisions : 91 - Repealed, SOR/2017-137,92 - (1) The consignor must classify these dangerous goods on the basis of samples.
(2) The consignor must make available to the Minister, on reasonable notice given by the Minister, a document that explains the sampling method and includes the following information:
(a) the scope of the method;
(b) the sampling apparatus;
(c) the sampling procedures;
(d) the frequency and conditions of sampling; and
(e) a description of the quality control management system in place, 150 - An approved ERAP is required for the dangerous goods referred to in paragraph 7.2(1)(f) of Part 7 (Emergency Response Assistance Plan).

Explosive Limit and Limited Quantity Index : 5 L

Excepted quantities (TDG) : E1

Passenger Carrying Road Vehicle or Passenger : 60 L

Carrying Railway Vehicle Index

Emergency Response Guide (ERG) Number : 128

IMDG

Special provision (IMDG) : 223, 955

Limited quantities (IMDG) : 5 L

Excepted quantities (IMDG) : E1

Packing instructions (IMDG) : P001, LP01

IBC packing instructions (IMDG) : IBC03

Tank instructions (IMDG) : T4

Tank special provisions (IMDG) : TP1, TP29

EmS-No. (Fire) : F-E - FIRE SCHEDULE Echo - NON-WATER-REACTIVE FLAMMABLE LIQUIDS

EmS-No. (Spillage) : S-E - SPILLAGE SCHEDULE Echo - FLAMMABLE LIQUIDS, FLOATING ON WATER

Stowage category (IMDG) : A

Properties and observations (IMDG) : Immiscible with water.

IATA

Special provision (IATA) : A3

PCA Excepted quantities (IATA) : E1

PCA Limited quantities (IATA) : Y344

PCA limited quantity max net quantity (IATA) : 10L

PCA packing instructions (IATA) : 355

PCA max net quantity (IATA) : 60L

CAO packing instructions (IATA) : 366

CAO max net quantity (IATA) : 220L

ERG code (IATA) : 3L

Document Number: 2009238

Document Version: 06

Document Part: 000

Document Status: Released

REMOVE – Universal Adhesive Remover

Safety Data Sheet

according to Federal Register / Vol. 89, No. 98 / Monday, May 20, 2024 / Rules and Regulations

SECTION 15 Regulatory information

15.1. Federal regulations

REMOVE – Universal Adhesive Remover

SARA Section 311/312 Hazard Classes	Physical hazard - Flammable (gases, aerosols, liquids, or solids) Health hazard - Carcinogenicity Health hazard - Aspiration hazard
-------------------------------------	---

Commercial status of components according to the United States Environmental Protection Agency's Toxic Substances Control Act (TSCA):

Name	CAS-No.	Listing	Commercial status	Flags
Naphtha (petroleum), hydrotreated heavy	64742-48-9	Present	Active	
Alkanes, C9-12-iso-	90622-57-4	Not present	-	
Propanol, 1(or 2)-(2-methoxymethylethoxy)-	34590-94-8	Present	Active	
2-Propanol, 1-(2-methoxypropoxy)-	13429-07-7	Not present	-	
Benzenemethanol	100-51-6	Present	Active	

15.2. International regulations

CANADA

Naphtha (petroleum), hydrotreated heavy (64742-48-9)

Listed on the Canadian DSL (Domestic Substances List)

Alkanes, C9-12-iso- (90622-57-4)

Listed on the Canadian DSL (Domestic Substances List)

Propanol, 1(or 2)-(2-methoxymethylethoxy)- (34590-94-8)

Listed on the Canadian DSL (Domestic Substances List)

2-Propanol, 1-(2-methoxypropoxy)- (13429-07-7)

Not listed on the Canadian DSL (Domestic Substances List)/NDSL (Non-Domestic Substances List)

Benzenemethanol (100-51-6)

Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations

No additional information available

Document Number: 2009238
Document Version: 06

Document Part: 000
Document Status: Released

REMOVE – Universal Adhesive Remover

Safety Data Sheet

according to Federal Register / Vol. 89, No. 98 / Monday, May 20, 2024 / Rules and Regulations

National regulations

Naphtha (petroleum), hydrotreated heavy (64742-48-9)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

Alkanes, C9-12-iso- (90622-57-4)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

Propanol, 1(or 2)-(2-methoxymethylethoxy)- (34590-94-8)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

Benzenemethanol (100-51-6)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

15.3. State regulations

No additional information available

SECTION 16 Other information

according to Federal Register / Vol. 89, No. 98 / Monday, May 20, 2024 / Rules and Regulations

Revision date : 1/14/2025

Issue date : 1/14/2025

Full text of hazard classes and H-statements

H226	Flammable liquid and vapor
H302	Harmful if swallowed
H304	May be fatal if swallowed and enters airways
H317	May cause an allergic skin reaction
H319	Causes serious eye irritation
H340	May cause genetic defects.
H350	May cause cancer.

Safety Data Sheet (SDS), USA

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

Document Number: 2009238
Document Version: 06

Document Part: 000
Document Status: Released