



1. Loading the needle – slide needle through rear opening; ensure that needle hook is seated into distal slot.



2. Operating the jaw – open jaw by depressing button on handle; close jaw by depressing loop on handle.



3. Loading the suture – form a suture loop, leaving approximate 2" tail. Position loop over suture loading slot and slide suture into the channel, ensuring that tail end is threaded DOWN through slot.



The performance you want. The reliability you expect.



Successful procedures are accomplished with skilled hands and dependable instruments.

Designed specifically for rotator cuff procedures, the TRUEPASS Suture Passer offers surgeons the reliability and performance synonymous with our legendary line of hand instrumentation. Simple, one-handed operation and precise control over jaw positioning can help your procedures run smoothly, and simultaneous suture passing and retrieval makes the suture passing step technically easier.

Reliably pass and retrieve #2 ULTRABRAID°

Suture or ULTRATAPE, in one easy motion*

Simple to load, operate and manage sutures

Innovative design allows for tissue manipulation and suture passage through cuff tissue, up to 10 mm in thickness

Ergonomically designed for one-handed operation and optimal maneuverability

*Data on file at Smith & Nephew in report 15002182.

Self-capture door

facilitates simultaneous suture passing and retrieval

Front loading slot

enables quick and easy loading of suture

ick and easy loading of



Polymer-coated needle


aids smooth passage through tissue, protecting the needle and helping to prevent breakage

Combination loop & button ratchet control

delivers precise control over jaw positioning and tensioning/grasping

Rear-handled deployment

functions smoothly with intuitive one-handed operation



Technique



1. Position on rotator cuff tendon at desired site and close jaws.



2. Squeeze rear handle to deploy needle and pass suture. Release rear handle to retract needle, leaving suture loop passed through tendon.





3. Depress forward button to disengage jaw (suture is retained by self-capture door) and remove device from joint space.



4. Remove captured suture by pulling suture loop upward and out to the right, lifting self-capture door and allowing suture to exit through side window.

Ordering Information

TRUEPASS Suture Passer

Reference #	Description
72203791	TRUEPASS Suture Passer, Self-Capture
72203792	TRUEPASS Suture Passer, Standard
72203793	TRUEPASS Disposable Needles (box of 5)

Smith & Nephew, Inc. 150 Minuteman Road Andover, MA 01810

www.smith-nephew.com T +1 978 749 1000 US Customer Service: +1 800 343 5717 International Customer Service: +1 978 749 1140 For more information, contact your sales representative or visit smith-nephew.com.